

ISO 9001:2000

PANEL AIR FILTERS


PANEL AIR FILTERS

Filtration Systems makes a wide range of panel air filters for engine air intake and operator/cab applications.

The large engine panels are reinforced for heavy duty use. They feature a washable media and a resilient “Poron” gasket for extended service life. Flame-retardant, high flow and water-repellant media are available, to fit your specific requirements.


Each filter is heat-cured in automated pneumatic presses to produce perfectly square, rigid panels. Our frames are formed in-house from coil stock for good availability and cost-control.

Our cab panels have a specially-designed media for high efficiency and low restriction to flow. All Filtration Systems panel filters have pleat packs made on our new computer-controlled pleaters producing sharp pleats for optimum performance.



Computer-Controlled Pleater

- A** “Tongue-in-Groove” corner construction for rigid, square frames with a smooth gasket sealing surface.
- B** Pleated media is washable for repeated use. Our computer-controlled machines assure uniform pleat spacing for optimum performance.
- C** Corrosion-resistant expanded metal screen protects the media. Large engine panels also have reinforcing strips for added strength.




Uniform Pleat Packs

AIR FILTER MEDIA

Filtration Systems has several grades of air filter media, from cellulose-paper to synthetics and our new nano-fiber laminates. All are washable, for extended service life.

Our cab panel media is designed for low flow restriction, while our turbine engine media is blended for high efficiencies and rupture strength. Our reciprocating-engine media is available with a flame-retardant treatment and water-repellant media is also offered for humid outdoor installations.




Cellulosic Filter Media (500x)

Clean Pressure Drop vs. Flow

19.5" x 19.5" Panel w/75 ft² media area


SWRI-96



Dust Holding Capacity

Per SAE J726-87

SWRI-96



Nomenclature Chart:

FS-AP-19252-G

FILTRATION SYSTEMS

MEDIA	
AP	Paper
APP	Polyester

OPTIONS	
G	Gasket
M	Molded
FR	Flame Retardant
HF	High-Flow
WR	Water Repellant
CM	Charge-Modified

LENGTH	
15	15.0"
16	16.0"
19	19.5"
24	24.0"
25	25.5"
32	32.0"
36	36.0"
47	47.0"

(other sizes avail.)

WIDTH <small>(if <10", ≥ 10")</small>	
15	15.0"
16	16.0"
19	19.5"
24	24.0"
25	25.5"
32	32.0"
60	6.0"
75	7.5"

(other sizes avail.)

DEPTH	
1	1.0"
2	2.19"
3	3.0"
5	5.0"



ISO 9001:2000



LOCAL DISTRIBUTOR:

W229 N591 Foster Court • Waukesha, WI 53186
 Phone: 262.548.6210 • FAX: 262.548.6239

Visit our website at www.filtersys.com or
 email us at sales@filtersys.com

Tradenames are for reference only.
 FSI reserves the right to alter any published data without notice.

PRINTED IN USA